



08-03-00

A

THOMPSON
HINE & FLORY LLP

Attorneys at Law

August 2, 2000



In re Application of:

Inventor(s) : Yan et al.
Filed : Herewith
Title : BELT TENSIONING DEVICE
Docket : 006593-01874

BOX PATENT APPLICATION

Assistant Commissioner for Patents
Washington, D.C. 20231

U.S. EXPRESS MAIL AIRBILL NO.
EM103840055US

Sir:

Enclosed are the following papers:

☒ Postcard
☒ Specification, Claims and Abstract, 11 page total.
☒ Drawings: 8 sheets. (Informal).
☒ Declaration (Executed).
☒ A check in the amount of \$ 768 .00 is enclosed, based upon the calculation below.


Basic Fee					\$ 690.00
Total Claims	20 - 20 = <u>0</u>	x	\$ 18.00	= \$.00
Independent Claims	4 - 3 = <u>1</u>	x	\$ 78.00	= \$	78.00
Charge for multiple dependent claims			\$260.00	= \$.00
TOTAL FEES DUE					\$ 768.00

The applicant(s) authorizes the Commissioner under 37 C.F.R. §1.136(a)(3) to treat any paper that is filed in this application which requires an extension of time as incorporating a request for such an extension.

Applicant(s) further authorizes the Commissioner to charge any additional fees required (including the fee for any additional extension of time) to Deposit Account No. 20-0809.

Respectfully submitted,

By:


Steven J. Elleman Reg. No. 41,733
(937) 443-6838

BELT TENSIONING DEVICE

BACKGROUND OF THE INVENTION

5 The present invention is directed to a belt tensioning device, and more particularly, to a device for tensioning a belt to a predetermined tension.

10 A variety of machines, mechanisms and other apparatuses use belt and pulley systems to transfer power between two or more rotating components. The belt in such a system is passed around two or more of the pulleys, and is preferably maintained at a specific, predetermined
15 tension. The belt tension should be high enough that the belt does not slip and therefore efficiently transfers power between the pulleys, but the tension should not be so high as to overload the belt.

20 In food processing machinery, particularly slicers, the belt/pulley system is often located deep inside the frame of the slicer. Accordingly, it is desirable to easily, accurately and precisely tension the belt in the slicer to reduce the need to access the belt/pulley system.

SUMMARY OF THE INVENTION

25 The present invention is a belt tensioning device which adjusts a belt to a precise, repeatable tension. The invention also has relatively few parts, and is inexpensive. When using the present invention, the belt can be tensioned to a specified tension without the use of a gauge or other special tools. The invention can be used to accurately set the belt tension during assembly of the associated mechanism or machine. The invention can also be used to tension the belt in the field, for example after disassembling the machine for maintenance.

30 In a preferred embodiment, the invention is a belt tensioning device for shifting a pulley such that a belt passed around the pulley is tightened to a predetermined tension. The device includes a rod coupled to the pulley, a member coupled to and movable along the rod, and a spring that exerts a reactive force against the member when the member is moved in a first direction along the rod. The device further includes a spacer which engages the member to limit

the advancement of the member in the first direction.

Other objects and advantages of the present invention will be apparent from the following description and the accompanying drawings.

5 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a slicer including the belt tensioning device of the present invention;

Fig. 2 is a bottom view of the slicer of Fig. 1, with part of the slicer removed to reveal part of the belt tensioning device of the present invention;

10 Fig. 3 is a partial cutaway bottom view of the slicer of Fig. 1, showing part of the belt tensioning device of the present invention;

Fig. 4 is a schematic representation of the belt tensioning device of the present invention, shown in an un-tensioned state;

Fig. 5 is a schematic representation of the device of Fig. 3, shown in a fully tensioned state;

Fig. 6 is a schematic representation of the belt tensioning device of the present invention shown in an alternate location and in its fully tensioned state;

Fig. 7 is an alternate embodiment of the belt tensioning device of the present invention shown in its un-tensioned state; and

20 Fig. 8 is a perspective, partial cutaway view of a mixer including the belt tensioning device of the present invention.

DETAILED DESCRIPTION

25 As shown in Figs. 1 and 2, the belt tensioning device of the present invention can be used in a slicer, generally designated 10. The slicer 10 includes a slicer body 12 and a tray 14 for receiving a food product (not shown). The tray 14 is reciprocatingly mounted on the slicer body 12 to bring a food product located on the tray into and out of contact with a rotating blade 16.

The slicer 10 also includes a motor for driving the blade 16.

As shown in Figs. 2-5, the motor 20 of the slicer 10 is pivotally mounted about a pivot rod 22 by a bracket 24. The pivot rod 22 is preferably stationary and coupled to the body 12 of the slicer 10. The motor 20 includes an output pulley 26 that is rotatably driven by the motor, and the output pulley 26 is coupled to a driven pulley 28 by a belt 30. The driven pulley 28 is directly or indirectly coupled to the blade 16 such that rotation of the blade 16 is driven by the motor 20. The output pulley 26 may also drive various other components in the slicer 10, such as the reciprocation of the tray 14 or other functions.

The belt tensioning device 11 includes an arm 32 that is coupled to the motor 20, and a threaded rod 34 is coupled to the arm 32. As shown in Fig. 3, in one embodiment the threaded rod 34 terminates in an eyelet 60 that receives a rod 62 therethrough, to couple the threaded rod and the arm 32. In Figs. 4-5, the connection between the rod 34 and arm 32 is schematically illustrated as connection 51. The threaded rod 34 extends through an opening 36 in a wall 38. A lock nut 40 is threaded onto the threaded rod 34 on one side of the wall 38, and a nut 42 is threaded onto the rod 34 on the other side of the wall 38. The belt tensioning device 11 includes a spacer 44 which generally receives a spring 46 therein. The spring 46 in turn receives the threaded rod 34 therethrough. The spacer 44 is preferably a hollow tube, and a washer 50 is located between the nut 42 and the spacer 44.

In its state shown in Fig. 4, the belt tensioning device 11 is disengaged and the belt 30 is generally slack. In order to tension the belt 30, the nut 42 is threaded along the rod 34 towards the wall 38. As the nut 42 and washer 50 are moved along the rod 34, the nut and washer engage the spring 46 located inside the spacer 44, and begin to compress the spring 46. As the spring 46 is compressed, it exerts a reactive force on the nut 42 and washer 50. The reactive force causes the threaded rod 34 to be pulled through the wall 38 towards the wall 38, and the motor 20 is rotated about the pivot rod 22 in the direction of arrow A. This movement of the motor 20 causes the tension in the belt 30 to increase.

The nut 42 and washer 50 are continued to be advanced onto the threaded rod 34 towards

the wall 38 (thereby further compressing the spring 46 and tensioning the belt 30) until the nut/washer engage the spacer 44 (Fig. 5). The spacer 44 provides a positive force feedback to let the user know that the nut/washer has engaged the spacer 44, and to stop advancing the nut 42 and washer 50 along the threaded rod 34. At this point, the desired tension in the belt 30 has been achieved. The lock nut 40 may then be threaded along the rod 34 towards the wall 38, until the lock nut 40 engages the wall 38, to further lock the belt tensioning device 11 in place. It should be noted that the rotation of the motor 20 in the direction of arrow A causes lateral movement of the rod 34 (i.e. left and right motion in Figs. 4 and 5), and the opening 36 should be wide enough to accommodate the expected range of lateral movement. In one embodiment, the opening 36 is generally elliptical, and is wide enough accommodate the expected lateral movement of the rod 34.

The length of the spacer 44 and the spring constant of the spring 46 can be selected to ensure that the desired tension of the belt 30 is consistently and repeatedly achieved each time the belt tensioning device 11 is utilized. Accordingly, the belt tensioning device 11 of the present invention tightens the belt 30 to a specified tension without requiring the use of gauges or other special tools, and the belt tensioning device 11 need only be assembled in the above-described manner to ensure that the belt 30 is properly tensioned. Furthermore, the spring 46 of the present invention is located between the wall 38 and the washer 50. Because the wall 38 is a fixed component, the belt tensioning device 11 provides a high degree of control over the spring deflection 46, and thereby the tension in the belt 30. Additionally, the belt tensioning device 11 minimizes bending moments in the system.

In an alternate embodiment, the arm 32 may comprise a variety of lever arms (not shown) to change the leverage of the arm 32 on the rotation of the motor 20 (and thereby optimize the force on the belt 30), or to change the moment arm ratios in the system. Furthermore, a variety of lever arms may be used to change the rotation of the motor 20; that is, a lever arm may be provided to rotate the motor in the opposite direction of arrow A when the nut 42 is tightened down.

The present invention may be implemented in a wide variety of manners beyond the specific embodiment shown herein. For example, although the spring 46 is preferably received within the spacer 44, it may be located at a variety of locations outside of the spacer.

Furthermore, the wall 38 may be replaced with any various type of anchor mechanism, so long as the anchor mechanism provides a surface for opposing the spring force and/or the force exerted by the spacer 44 when the nut 42 and washer 50 engage the spacer. Furthermore, besides the nut/threaded rod arrangement, nearly any mechanism or member besides the nut that can clamp onto or otherwise engage a rod or other member while compressing the spring 46, may be used. Finally, although the spacer 44 is preferably located around the threaded rod 34, the spacer need not be a tube, and need not be located around the threaded rod.

In a preferred embodiment, the uncompressed length of the spring 46 is about 18 mm, the spring constant is about 28 N/mm, and the outer diameter of the spring is about 12 mm. The spacer 44 is about 12 mm long in this embodiment such that the spring 46 is compressed by 6 mm. The reaction force (i.e., the force exerted by the spring 46 on the washer 50) in this case is expected to be about 168 N, which results in a belt tension of about 150 N. Of course, these specifications and dimensions are for one embodiment only, and a variety of sizes and shapes of the various components of the invention may be used without departing from the scope of the invention.

In some cases, due to space or accessibility requirement, the belt tensioning device 11 may be located on the opposite side of the arm 32 from that shown in Figs. 4-5. This embodiment is shown in Fig. 6.

Fig. 7 illustrates an alternate embodiment of the invention. The belt tensioning device 11' includes a threaded rod 34' that is anchored to the body of the machine. The arm 32 of the motor 20 is coupled to the threaded rod 34' by a collar 33 that fits loosely around the threaded rod 34'. The collar 33 is free to move up and down the length of the rod 34', and the collar 33 is preferably pivotably coupled to the arm 32 to allow the collar 33 to pivot relative to the arm as the collar moves along the length of the rod.

In order to tension the belt 30 in the device of Fig. 7, the nut 42 is threaded along the rod 34 towards the wall 36. The nut 42 then engages the collar 33 and washer 50 and urges them towards the wall 36. This causes the motor 20 to pivot in the direction of arrow A, thereby tensioning the belt 30. The sleeve 44 provides a force feedback when the washer 50 engages the sleeve 44 to provide an indication that the belt 30 is tensioned to the proper tension. The lock nut 40 may then be tightened against the wall 38 to lock the device 11' in place.

Although the belt tensioning device 11 of the present invention is illustrated and described in conjunction with a slicer, it should be understood that the belt tensioning device may be used with nearly any system having a pivotable pulley with a belt passed around the pulley. For example, the belt tensioning device 11 may be used with a mixer 70 as shown in Fig. 8. The mixer 70 includes a mixer body 72, a mixer bowl 74, and a rotatable output component 76. The rotatable output component 76 can releasably receive a mixing element 78. The output component 76 is coupled to a pulley 77, which is in turn directly or indirectly coupled to the output pulley 83 of a motor 80 by a belt 81. In this manner the motor 80 can rotate the output component 76 and mixing element 78 to mix the contents of the bowl 74. The motor 80 is pivotably mounted onto a rod 82, and arm 32 and threaded rod 34 portions of the belt tensioning device 11, which can cause the motor 80 to pivot about rod 82 to tension the belt 81, can be seen. The remainder of the belt tensioning device is the same as the belt tensioning device 11 disclosed and described above.

Having described the invention in detail and by reference to the preferred embodiments, it will be apparent that modifications and variations thereof are possible without departing from the scope of the invention.

What is claimed is:

1. A belt tensioning device for shifting a pulley such that a belt passed around said pulley can be tightened to a predetermined tension comprising:
 - a rod coupled to said pulley;
 - a member coupled to and movable along said rod;
 - a spring that exerts a reactive force against said member when said member is moved in a first direction along said rod; and
 - a spacer which engages said member to limit the advancement of said member in said first direction.
2. The device of claim 1 wherein said rod is a threaded rod, and said member is a nut threaded onto said threaded rod.
3. The device of claim 1 wherein said pulley is located adjacent an anchor component having an opening formed therein, and wherein said rod extends through said opening.
4. The device of claim 3 wherein said anchor component is a wall.
5. The device of claim 3 wherein said spring is located between said member and said anchor component.
6. The device of claim 3 wherein said spacer is located between said member and said anchor component.
7. The device of claim 3 wherein said first direction is towards said anchor component.
8. The device of claim 3 wherein said spring, said spacer, and said member are located on a first side of said anchor component, and wherein the device further comprises a lock nut

located on a second side of said anchor component to secure said threaded rod in place.

9. The device of claim 1 wherein said rod extends through said spring.
10. The device of claim 1 wherein said rod extends through said spacer.
11. The device of claim 1 wherein said spacer receives said spring therein.
12. The device of claim 1 wherein said pulley is pivotably mounted such that advancement of said member in said first direction causes said spring to be compressed, which in turn causes said pulley to be pivoted and the tension in said belt thereby increased.
13. The device of claim 1 further comprising an arm having a first end and a second end, said first end being coupled to said rod and said second end being coupled to said pulley.
14. The device of claim 1 wherein when said rod includes a lever mechanism to vary the force applied upon said pulley as said member is moved along said rod.
15. A belt tensioning device for shifting a pulley such that a belt passed around said pulley can be tightened to a predetermined tension comprising:
 - a rod;
 - an arm coupled to said pulley, said arm being movable along said rod;
 - a spring that exerts a reactive force against said arm when said arm is moved in a first direction along said rod; and
 - a spacer which engages said arm to limit the advancement of said arm in said first direction.

16. The device of claim 15 further comprising a member coupled to said rod that engages said arm and causes said arm to move in said first direction.

17. The device of claim 16 wherein said rod is a threaded rod and said member is a nut threaded onto said rod.

18. The device of claim 15 wherein said arm includes a collar that fits around said rod.

19. A slicer comprising:

a slicer body;

a rotatable blade coupled to said slicer body;

a reciprocal tray for bringing a food product into and out of contact with said blade;

a motor for driving said blade, said motor being pivotable and having an output pulley operatively connected to said blade; and

a belt tensioning device for said motor such that a belt passed around said output pulley can be tightened to a predetermined tension, the belt tensioning device including a threaded rod coupled to said motor, said rod being located adjacent an anchor component, a nut threaded onto said threaded rod, a spring located adjacent said nut that exerts a reactive force against said nut when said nut is threaded in a first direction along said rod to cause said motor to pivot, and a spacer which engages said nut to limit the advancement of said nut in said first direction.

20. A mixer comprising:

a mixer body having a rotatable output component;

a bowl that is mountable onto said mixer body;


a motor for rotating said output component, said motor being pivotable and

having an output pulley operatively connected to said output component; and

a belt tensioning device for said motor such that a belt passed around said output pulley can be tightened to a predetermined tension, the belt tensioning device including a threaded rod coupled to said motor, said rod being located adjacent an anchor component, a nut threaded onto said threaded rod, a spring located adjacent said nut that exerts a reactive force against said nut when said nut is threaded in a first direction along said rod to cause said motor to pivot, and a spacer which engages said nut to limit the advancement of said nut in said first direction.

5

138601



FE 1

Third Angle Projection

101188
 101189
 101190
 101191
 101192
 101193
 101194
 101195
 101196
 101197
 101198
 101199
 101200
 101201
 101202
 101203
 101204
 101205
 101206
 101207
 101208
 101209
 101210
 101211
 101212
 101213
 101214
 101215
 101216
 101217
 101218
 101219
 101220
 101221
 101222
 101223
 101224
 101225
 101226
 101227
 101228
 101229
 101230
 101231
 101232
 101233
 101234
 101235
 101236
 101237
 101238
 101239
 101240
 101241
 101242
 101243
 101244
 101245
 101246
 101247
 101248
 101249
 101250
 101251
 101252
 101253
 101254
 101255
 101256
 101257
 101258
 101259
 101260
 101261
 101262
 101263
 101264
 101265
 101266
 101267
 101268
 101269
 101270
 101271
 101272
 101273
 101274
 101275
 101276
 101277
 101278
 101279
 101280
 101281
 101282
 101283
 101284
 101285
 101286
 101287
 101288
 101289
 101290
 101291
 101292
 101293
 101294
 101295
 101296
 101297
 101298
 101299
 101300
 101301
 101302
 101303
 101304
 101305
 101306
 101307
 101308
 101309
 101310
 101311
 101312
 101313
 101314
 101315
 101316
 101317
 101318
 101319
 101320
 101321
 101322
 101323
 101324
 101325
 101326
 101327
 101328
 101329
 101330
 101331
 101332
 101333
 101334
 101335
 101336
 101337
 101338
 101339
 101340
 101341
 101342
 101343
 101344
 101345
 101346
 101347
 101348
 101349
 101350
 101351
 101352
 101353
 101354
 101355
 101356
 101357
 101358
 101359
 101360
 101361
 101362
 101363
 101364
 101365
 101366
 101367
 101368
 101369
 101370
 101371
 101372
 101373
 101374
 101375
 101376
 101377
 101378
 101379
 101380
 101381
 101382
 101383
 101384
 101385
 101386
 101387
 101388
 101389
 101390
 101391
 101392
 101393
 101394
 101395
 101396
 101397
 101398
 101399
 101400
 101401
 101402
 101403
 101404
 101405
 101406
 101407
 101408
 101409
 101410
 101411
 101412
 101413
 101414
 101415
 101416
 101417
 101418
 101419
 101420
 101421
 101422
 101423
 101424
 101425
 101426
 101427
 101428
 101429
 101430
 101431
 101432
 101433
 101434
 101435
 101436
 101437
 101438
 101439
 101440
 101441
 101442
 101443
 101444
 101445
 101446
 101447
 101448
 101449
 101450
 101451
 101452
 101453
 101454
 101455
 101456
 101457
 101458
 101459
 101460
 101461
 101462
 101463
 101464
 101465
 101466
 101467
 101468
 101469
 101470
 101471
 101472
 101473
 101474
 101475
 101476
 101477
 101478
 101479
 101480
 101481
 101482
 101483
 101484
 101485
 101486
 101487
 101488
 101489
 101490
 101491
 101492
 101493
 101494
 101495
 101496
 101497
 101498
 101499
 101500
 101501
 101502
 101503
 101504
 101505
 101506
 101507
 101508
 101509
 101510
 101511
 101512
 101513
 101514
 101515
 101516
 101517
 101518
 101519
 101520
 101521
 101522
 101523
 101524
 101525
 101526
 101527
 101528
 101529
 101530
 101531
 101532
 101533
 101534
 101535
 101536
 101537
 101538
 101539
 101540
 101541
 101542
 101543
 101544
 101545
 101546
 101547
 101548
 101549
 101550
 101551
 101552
 101553
 101554
 101555
 101556
 101557
 101558
 101559
 10







FIG 2

09630433.000000



002080" 2040E960





002080" 2040E960

002080" 2040E950




FIG. 6



1/2




FIG. 7

002080" 2040E960

002080" 20702960




FIG. 8

DECLARATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am an original, first and joint inventor of the invention entitled:

BELT TENSIONING DEVICE

described and claimed

 X in the attached specification;
 in the specification filed _____,
as U.S. Application Serial No. _____
and as amended _____.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as filed and as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

Send Correspondence To:

Mark P. Levy
Thompson Hine & Flory LLP
2000 Courthouse Plaza NE
P.O. Box 8801
Dayton, Ohio 45401-8801

Direct Telephone Calls To:

Mark P. Levy
(937) 443-6949

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

006593-1874

Full name of first Inventor - Gongpu Yan

Inventor's Signature Gongpu Yan

Date: July 31, 2000

Residence: 160 Fox Harbor Drive, Troy, Ohio 45373

Citizenship : US

Post Office Address: c/o Hobart Corporation
701 Ridge Avenue
Troy, Ohio 45374-0001

Full name of second Inventor - Anthony L. DeBrosse

Inventor's Signature Anthony L. DeBrosse

Date: 7-31-00

Residence: 1504 Sweetbriar Ave, Piqua, Ohio 45356

Citizenship : US

Post Office Address: c/o Hobart Corporation
701 Ridge Avenue
Troy, Ohio 45473-0001

144608.1